

SmartPad™ Remote control for CMMs



Product description

The SmartPadTM provides multi-functional and comprehensive CMM operation with user-friendly wireless connection. Thanks to the open programmability of the SmartPadTM, the user interface, functions and interactions with the CMM software can individually be programmed. The capacitive 4.3° color LCD display shows all information at a glance, and features single touch technology that ensures mooth and easy operation. With optimal functionality, SmartPadTM ensures ideal measurement processes.

System integration

The SmartPadTM operating unit is intended for the use with the EAGLETM and CONDORTM controller range. For tailor made GUIs Pantec provides a software development kit (SDK).

Technical Specifications

Technical parameter

• Operating system Windows Embedded Compact 7

Display Capacitive color 4.3" LCD with single touch

• Function keys pre-defined

Connection
 Safety
 Power supply
 Peer to peer over TCP / IP
 Plc according to DIN EN 13849
 4.4 Ah Li-Ion battery / external supply

Recharge Via power cord / external recharger

Dimensions (LxHxW)
 Weight
 Speed regulation
 209 x 102 x 137 mm
 640 g (incl. battery)
 Override potentiometer

System recovery Reset button

Machine status real time displayed
 ✓
 Protection class

Firmware updates Via Pantec Support Tool

Product configuration

• SmartPad™ Starter Kit SmartPad™, WLANrouter, charger, adapter

■ SmartPad™

Options

Adapter

Cradle
 SmartPad™ evaluation
 Li-Ion battery
 External charger
 Cradle with charger
 For software development, Ethernet connection
 4.4 Ah, rechargeable
 External charger
 24390
 2 charging compartments + 5V input

23932

HQ/International
Pantec Engineering AG
Industriering 21
9491 Ruggell
Principality of Liechtenstein
Phone +423 377 13 33
Fax +423 377 13 34

China
Pantec (Shanghai) Co., Ltd.
128 Shenfu Road; Building Nr. 18
Xinzhuang, Industry Park
201108 Shanghai, China
Phone +86 21 517 60 282
Fax +86 21 517 60 281

Switzerland
Pantec GS Systems AG
Heldswilerstrasse 13
9214 Kradolf
Switzerland
Phone +41 71 644 98 98
Fax +41 71 644 98 99

90 - 260 VAC + 5VDC / 2 A

